Appl. No. 10/731,683
Response to Restriction and Election of Species
Requirements dated February 7, 2007
Reply to Restriction Requirement of January 9, 2007

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

- 1. 19. (canceled)
- 20. (original) A system for enhancing minimally invasive heart surgery, the system comprising:
- at least one retractor device for enhancing access to a patient's heart through a first incision:
- a heart stabilizing device having a tissue contacting surface and at least one suction aperture adjacent the surface; and
- a first coupling device for coupling with the heart stabilizing device through a second incision at a location on the patient apart from the first incision.
 - 21. (original) A system as in claim 20, further comprising:
- a heart positioning device having a tissue contacting surface and at least one suction aperture; and
- a second coupling device for coupling with the heart positioning device through a third incision at a location on the patient apart from the first and second incisions.
- 22. (original) A system as in claim 21, wherein the first and second coupling devices each comprise an elongate shaft having a proximal end, a distal end and means for coupling with the heart stabilizing device or the heart positioning device adjacent the distal end.
- 23. (original) A system as in claim 22, wherein the means for coupling comprises a collet or socket for coupling with a ball on the heart stabilizing device or the heart positioning device.

Appl. No. 10/731,683
Response to Restriction and Election of Species
Requirements dated February 7, 2007
Reply to Restriction Requirement of January 9, 2007

- 24. (original) A system as in claim 23, wherein each of the first and second coupling devices further include a tightening device adjacent the proximal end of the shaft, for tightening the collet or socket around the ball.
- 25. (original) A system as in claim 22, wherein the means for coupling comprises a slot for coupling with a surface feature on the heart stabilizing device or the heart positioning device.
- 26. (original) A system as in claim 22, wherein the means for coupling comprises threads for coupling with complementary threads on the heart stabilizing device or the heart positioning device.
- 27. (original) A system as in claim 22, wherein the means for coupling comprises a clamp for coupling with the heart stabilizing device or the heart positioning device.
- 28. (original) A system as in claim 22, wherein the elongate shaft comprises at least one flexible joint between the proximal end and the distal end.
- (original) A system as in claim 28, wherein the at least one flexible joint comprises at least one collet or socket and ball joint.
- (original) A system as in claim 22, wherein the elongate shaft comprises at least one flexible, rigidifying portion.
- (original) A system as in claim 30, wherein the rigidifying portion is rigidified by applying suction.
 - 32. (original) A system as in claim 21, further comprising:
- a first flexible arm for coupling the first coupling device with at least one stable object; and
- a second flexible arm for coupling the second coupling device with the at least one stable object.

Appl. No. 10/731,683

Response to Restriction and Election of Species Requirements dated February 7, 2007

Reply to Restriction Requirement of January 9, 2007

- (original) A system as in claim 32, wherein the first and second flexible arms may be rigidified after coupling the first and second coupling devices with the stable object.
- 34. (original) A system as in claim 32, wherein the at least one stable object comprises at least one part of an operating room table.
- (original) A system as in claim 32, wherein each of the first and second 35. flexible arms comprises:

an elongate arm having a proximal end, a distal end and at least one joint disposed between the proximal end and the distal end;

> means near the distal end for coupling the arm with a coupling device; means near the proximal end for coupling the arm with the stable object; and means for rigidifying the at least one joint of the arm.

- 36 (original) A system as in claim 35, wherein the means near the distal end and the means near the proximal end each comprises a clamp.
- 37. (original) A system as in claim 20, wherein the at least one retractor device comprises:

a retractor frame for movably holding at least two retractor blades;

at least two retractor blades coupled with the retractor frame, for retracting tissue adjacent an incision; and

means for moving the retractor frame so as to move the blades to retract the tissue.

- (original) A system as in claim 37, wherein each of the at least two 38. retractor blades includes nerve protection means for inhibiting damage to an intercostal nerve when retracting a rib.
- (original) A system as in claim 37, wherein the means for moving the retractor frame comprises a crank handle.

Appl. No. 10/731,683

Response to Restriction and Election of Species Requirements dated February 7, 2007

Reply to Restriction Requirement of January 9, 2007

40. (original) A system as in claim 20, wherein the heart stabilizing device comprises:

at least one tissue contacting surface;

at least one suction aperture for applying suction force to enhance contact between the tissue contacting surface and heart tissue; and

at least one suction port for connecting with a source of suction.

41. (original) A device for enhancing minimally invasive heart surgery, the device comprising:

a surgical tool; and

an elongate coupling member having a proximal end, a distal end and means near the distal end for coupling with the surgical tool.

- (original) A device as in claim 41 wherein the surgical tool is a heart stabilizing member.
- 43. (original) A device as in claim 42, wherein the heart stabilizing member comprises:

at least one tissue contacting surface;

at least one suction aperture for applying suction force to enhance contact between the tissue contacting surface and heart tissue; and

at least one suction port for coupling with a source of suction.

- 44. (original) A device as in claim 42, wherein the heart stabilizing member comprises:
 - at least one inflatable tissue contacting surface; and
 - at least one port for allowing inflation of the tissue contacting surface.

Appl. No. 10/731,683

Response to Restriction and Election of Species Requirements dated February 7, 2007

Reply to Restriction Requirement of January 9, 2007

45. (original) A device as in claim 42, wherein the means for coupling with the heart stabilizing member comprises a collet or socket for coupling with a ball on the heart stabilizing member.

- 46. (original) A device as in claim 42, wherein the means for coupling with the heart stabilizing member comprises a clamp.
- 47. (original) A device as in claim 42, wherein the means for coupling with the heart stabilizing member comprises a slot for coupling with a surface feature on the heart stabilizing device or the heart positioning device.
- 48. (original) A device as in claim 42, wherein the means for coupling with the heart stabilizing member comprises threads for coupling with complementary threads on the heart stabilizing device or the heart positioning device.
- 49. (original) A device as in claim 42, wherein the means for coupling with the heart stabilizing member comprises a clamp.
- 50. (original) A device as in claim 42, wherein the elongate coupling member further includes at least one flexible joint between the proximal end and the distal end.
- 51. (original) A device as in claim 50, wherein the at least one joint comprises a collet or socket and ball joint.
- (original) A device as in claim 50, wherein the at least one joint comprises multiple flexible beads.
- (original) A device as in claim 41 wherein the surgical tool is a heart positioning member.
- 54. (original) A device as in claim 53, wherein the heart positioning member comprises:

Appl. No. 10/731,683
Response to Restriction and Election of Species
Requirements dated February 7, 2007
Reply to Restriction Requirement of January 9, 2007

at least one tissue contacting surface;

at least one suction aperture for applying suction force to enhance contact between the tissue contacting surface and heart tissue; and

- at least one suction port for connecting with a source of suction.
- 55. (original) A device as in claim 53, wherein the heart positioning member comprises:
 - at least one inflatable tissue contacting surface; and
 at least one port for allowing inflation of the tissue contacting surface.
- 56. (original) A device as in claim 53, wherein the means for coupling with the heart positioning member comprises a collet or socket for coupling with a ball on the heart positioning member.
- (original) A device as in claim 53, wherein the means for coupling with the heart positioning member comprises a clamp.
- 58. (original) A device as in claim 53, wherein the elongate coupling member further includes at least one flexible joint between the proximal end and the distal end.
- (original) A device as in claim 58, wherein the at least one joint comprises a collet or socket and ball joint.
- (original) A device as in claim 58, wherein the at least one joint comprises multiple flexible beads.
- 61. (original) A device as in claim 41 wherein the surgical tool comprises: at least one inflatable tissue contacting surface; and at least one port coupled with the tissue contacting surface for allowing inflation of the surface.